

View Online at <https://aerobasegroup.com/nsn/4820-01-626-5089>

Body Material:

Bronze, astm b62

Body Style:

Straight thru

Media For Which Designed:

Water, oil or gas

First End Connection Type:

Threaded internal pipe

First End Style Designator:

Plain

First End Thread Size And Series/type Designator:

1/2-14 npt

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Seat Material:

Steel, mil-s-5059, type 302

Face To Face Distance:

3.88 inches

Flow Control Device:

Diaphragm

Flow Control Device Material:

Nickel copper alloy

End Connection Quantity:

2

Outlet Pressure Range:

+10.0 to 40.0 pounds per square inch

Regulation Type:

Automatic single stage

Manual Control Method:

Wrench

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

400.0 pounds per square inch

Outlet Pressure Setting:

30.0 pounds per square inch

Filter:

Not included

End Application:

Sentinel class fast response cutter b (frc-b)

Temperature Rating:

Between -20.0 degrees fahrenheit and 200.0 degrees fahrenheit

Valve Size:

0.50 inches

Product Name:

Pressure reducing regulator valve

Special Features:

Cms data id 4024 pccn se0732 plisn a001; used on potable water system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A21100