NSN 4820-01-628-3936

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-628-3936

Flow Control Device: Poppet Maximum Operating Temp: 275.0 degrees fahrenheit single response Minimum Operating Temp: -65.0 degrees fahrenheit Valve Size: 0.125 inches Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring material: buna n
Maximum Operating Temp: 275.0 degrees fahrenheit single response Minimum Operating Temp: -65.0 degrees fahrenheit Valve Size: 0.125 inches Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
275.0 degrees fahrenheit single response Minimum Operating Temp: -65.0 degrees fahrenheit Valve Size: 0.125 inches Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
Minimum Operating Temp: -65.0 degrees fahrenheit Valve Size: 0.125 inches Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
-65.0 degrees fahrenheit Valve Size: 0.125 inches Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
Valve Size: 0.125 inches Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
0.125 inches Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
Maximum Operating Pressure: 200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
200.0 pounds per square inch single response Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
Special Features: Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
Inline valve proof pressure: 400 psig; inline vlave burst pressure: above 500 psig; applications: refrigeration and heating equipment; o-ring
material: buna n
Material:
Steel comp 303 body
Style Designator:
Straight through note: to be used for valve bodies of one section only.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0