Shuttle Valve - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/4820-01-629-6290



| Flow Control Device:  |
|---|
| Poppet  |
| Valve Discharge Flow Rate:  |
| 6.0 gallons per minute  |
| Valve Operation Method:   |
| Automatic   |
| Maximum Operating Pressure:   |
| 40.0 pounds per square inch single response   |
| Product Name:   |
| High pressure spring biassed shuttle valve  |
| Special Features:   |
| Next higher assembly nlg door actuator, p/n 10-172701-001   |
| Material:   |
| Stainless steel   |
| Media For Which Designed:   |
| 5   |
| Oil, hydraulic single response  |
|   |
| Oil, hydraulic single response  |
| Oil, hydraulic single response Surface Treatment:   |
| Oil, hydraulic single response Surface Treatment: Anodize   |
| Oil, hydraulic single response Surface Treatment: Anodize Style Designator:   |
| Oil, hydraulic single response Surface Treatment: Anodize Style Designator: Cross   |
| Oil, hydraulic single response<br>Surface Treatment:<br>Anodize<br>Style Designator:<br>Cross<br>Shelf Life:                            |
| Oil, hydraulic single response<br>Surface Treatment:<br>Anodize<br>Style Designator:<br>Cross<br>Shelf Life:<br>N/a                     |
| Oil, hydraulic single response<br>Surface Treatment:<br>Anodize<br>Style Designator:<br>Cross<br>Shelf Life:<br>N/a                     |
| Oil, hydraulic single response Surface Treatment: Anodize Style Designator: Cross Shelf Life: N/a Unit Of Measure:                      |
| Oil, hydraulic single response Surface Treatment: Anodize Style Designator: Cross Shelf Life: N/a Unit Of Measure: Demilitarization:    |
| Oil, hydraulic single response Surface Treatment: Anodize Style Designator: Cross Shelf Life: N/a Unit Of Measure: Demilitarization: No |