

View Online at <https://aerobasegroup.com/nsn/4820-01-629-8628>

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

26.0 gallons per minute

Maximum Operating Temp:

120.0 degrees celsius single response

Minimum Operating Temp:

-40.0 degrees celsius

Connection Style:

Plain (screw-in cartridge) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded cartridge 1st end

Valve Size:

0.875 inches

Thready Qty Per Inch (tpi):

14 1st end

Adjustable Pressure Range:

+50.0 to 5000.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Product Name:

Pilot operated, balanced sliding spool, pressure relief cartridge type valve; adjustment capped; valve cavity c1020; seal replacement kit is p/n skn-1022

Special Features:

Media general purpose hydraulic fluid such as mil-h-5606, sae no. 10, sae no. 20, etc.

Material:

Rubber butadiene-acrylonitrile class nbr seat

Style Designator:

Screw-in cartridge

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0