NSN 4820-01-630-2086

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-630-2086

Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
121.0 degrees celsius single response
Minimum Operating Temp:
40.0 degrees celsius
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal tube all ends
Valve Size:
0.375 inches
Adjustable Pressure Range:
+40.0 to 125.0 pounds per square inch
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Outside Diameter Tube Accommodated:
0.375 inches all ends
Special Features:
In-line valve, size y internal straight threads
Material:
Stainless steel flow control device
Media For Which Designed:
Oil, hydraulic 2nd response
Surface Treatment:
Anodize
Style Designator:
Straight thru

NSN 4820-01-630-2086

Safety Relief Valve - Page 2 of 2



Thread Series Designator:

Si all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0