NSN 4820-01-632-0573

Ball Valve - Page 1 of 2

Bolt Hole Quantity:



View Online at https://aerobasegroup.com/nsn/4820-01-632-0573

| 8 all ends |
|--|
| Maximum Operating Temp: |
| 150.0 degrees fahrenheit single response |
| Current Rating In Amps: |
| 7.2 |
| Valve Operation Method: |
| Electric motor |
| Flange Shape: |
| Round with holes all ends |
| Connection Type: |
| Flange all ends |
| Valve Size: |
| 5.0 inches |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch single response |
| Voltage In Volts And Current Type: |
| 440.0 ac |
| Outside Diameter: |
| 10.00 inches all ends |
| Face To Face Distance: |
| 10.0 inches |
| Thickness: |
| 1.50 inches all ends |
| Bolt Hole Diameter: |
| 0.88 inches all ends |
| Bolt Circle Diameter: |
| 8.50 inches all ends |
| Flange Face Design: |
| Plain all ends |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Plastic polytetrafluoroethylene seat |
| Media For Which Designed: |
| Water, fresh single response |
| Style Designator: |
| Straight through flanged ends |
| Shelf Life: |
| N/a |
| |

NSN 4820-01-632-0573

Ball Valve - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A046b0