NSN 4820-01-645-1658

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-645-1658

Flow Control Device: Poppet Maximum Operating Temp: 250.0 degrees fahrenheit single response Valve Operation Method: Manual Valve Size: 0.375 inches Maximum Operating Pressure: 2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization:	
250.0 degrees fahrenheit single response Valve Operation Method: Manual Valve Size: 0.375 inches Maximum Operating Pressure: 2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Valve Operation Method: Manual Valve Size: 0.375 inches Maximum Operating Pressure: 2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Manual Valve Size: 0.375 inches Maximum Operating Pressure: 2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Valve Size: 0.375 inches Maximum Operating Pressure: 2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Maximum Operating Pressure: 2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Maximum Operating Pressure: 2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
2200.0 pounds per square inch single response Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Product Name: Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Poppet check valve Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Special Features: Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Connection type: swagelok? Tube fitting; temppresscode: 2-8cb; cracking pressure: 1/3 psi (0.03 bar, 0.003 surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
surface finish: standard; unspsc (swg01): 40141641; lubricant: dow vacuum Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Material: Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	mpa); o-rings: buna n;
Copper alloy Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:	
Straight thru Shelf Life: N/a Unit Of Measure:	
Shelf Life: N/a Unit Of Measure:	
N/a Unit Of Measure: 	
Unit Of Measure:	
 Demilitarization:	
Demilitarization:	
No	
Fiig:	
A530b0	