## NSN 4820-01-646-5459

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-646-5459

| Pipe Size Accommodated:  |
|--|
| 1.00 inches 2nd end  |
| Flow Control Device:   |
| Disk   |
| Bonnet Type:   |
| Inside spring  |
| Bonnet Attachment Method:  |
| Threaded   |
| Disk Loading Method:   |
| Spring   |
| Maximum Operating Temp:  |
| 406.00 degrees fahrenheit single response                                  |
| Length:  |
| 9.00 inches all ends   |
| Valve Operation Method:  |
| Manual   |
| Maximum Operating Pressure:  |
| 300.00 pounds per square inch single response                              |
| Opening Pressure Setting:  |
| 30.00 pounds per square inch   |
| First Connection Face To Centerline Distance:                              |
| 2.375 inches   |
| Second Connection Face To Centerline Distance:                             |
| 1.625 inches   |
| Product Name:  |
| Valve, angle relief  |
| Special Features:  |
| Male x female threaded or npt; packed lever;                               |
| Material:  |
| Stainless steel flow control device  |
| Material Specification:  |
| Astm b584 alloy 84400 national specification single material response body |
| Style Designator:  |
| Angle  |
| Furnished Items And Quantity:  |
| 1 lever  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 4820-01-646-5459

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0