## NSN 4820-01-646-5745

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-646-5745

Pipe Size Accommodated:
1.25 inches 2nd end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
406.00 degrees fahrenheit single response
Length:
9.375 inches all ends
Valve Operation Method:
Manual
Maximum Operating Pressure:
300.00 pounds per square inch single response
Opening Pressure Setting:
60.00 pounds per square inch
First Connection Face To Centerline Distance:
2.625 inches
Second Connection Face To Centerline Distance:
2.000 inches
Product Name:
Valve, angle relief
Special Features:
Male x female threaded npt; packed lever; valve service: liquid asme section viii;
Material:
Stainless steel flow control device
Material Specification:
Astm b584 alloy 84400 national specification single material response body
Style Designator:
Angle
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-01-646-5745

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0