# NSN 4820-01-646-5793

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-646-5793



## Pipe Size Accommodated:

1.50 inches 2nd end

## **Flow Control Device:**

Disk

# Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Threaded

# **Disk Loading Method:**

Spring

## Maximum Operating Temp:

406.00 degrees fahrenheit single response

#### Length:

10.50 inches all ends

## Valve Operation Method:

Manual

## Maximum Operating Pressure:

300.00 pounds per square inch single response

## **Opening Pressure Setting:**

60.00 pounds per square inch

# First Connection Face To Centerline Distance:

2.875 inches

# Second Connection Face To Centerline Distance:

2.375 inches

## **Product Name:**

Valve, angle relief

#### **Special Features:**

Male x female threaded npt; packed lever; valve service: liquid asme section viii;

## Material:

Stainless steel flow control device

## **Material Specification:**

Astm b584 alloy 84400 national specification single material response body

## Style Designator:

Angle

# Furnished Items And Quantity:

1 lever

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 4820-01-646-5793

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

