NSN 4820-01-647-8307

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:

0.50 inches all endsThread Direction:Right-hand all endsFlow Control Device:

Poppet

Bonnet Type:



View Online at https://aerobasegroup.com/nsn/4820-01-647-8307

Inside spring
Bonnet Attachment Method:
Threaded
Valve Discharge Flow Rate:
10.00 gallons per minute
Maximum Operating Temp:
250.00 degrees fahrenheit single response
End Application:
R20tmmasp-001
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Valve Size:
0.50 inches
Adjustable Pressure Range:
+10.0 to 50.0 pounds per square inch
Maximum Operating Pressure:
3600.00 pounds per square inch single response
Thread Size:
0.50 inches all ends
Opening Pressure Setting:
35.00 pounds per square inch
First Connection Face To Centerline Distance:
2.16 inches
Second Connection Face To Centerline Distance:
1.50 inches
Product Name:
Pressure control valve
Material:
Aluminum alloy body
Style Designator:
Angle

NSN 4820-01-647-8307

Safety Relief Valve - Page 2 of 2



Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0