NSN 4820-01-650-5385

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-650-5385

Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
800.00 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Maximum Operating Pressure:
1400.00 pounds per square inch single response
Thread Size:
1.00 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
1025.00 pounds per square inch
First Connection Face To Centerline Distance:
2.375 inches
Second Connection Face To Centerline Distance:
1.625 inches
Special Features:
Threaded cap
Material:
Steel stainless stem
Material Specification:
A479-316 assn standard single material response stem
Media For Which Designed:
Liquid single response
Style Designator:
Angle
Thread Series Designator:

Npt all ends

NSN 4820-01-650-5385

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0