NSN 4820-01-650-5386

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-650-5386 **Thread Direction:** Right-hand all ends **Flow Control Device:** Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 800.00 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 2nd end **Maximum Operating Pressure:** 1400.00 pounds per square inch single response **Thread Size:** 1.00 inches 2nd end Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 75.00 pounds per square inch **First Connection Face To Centerline Distance:** 2.375 inches **Second Connection Face To Centerline Distance:** 1.625 inches **Special Features:** Threaded cap Material: Steel stainless stem **Material Specification:** A479-316 assn standard single material response stem Media For Which Designed: Liquid single response **Style Designator:**

Thread Series Designator:

Angle

Npt all ends

NSN 4820-01-650-5386

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0