NSN 4820-01-653-1250

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Disk Loading Method:

Bonnet Type: Inside spring

Threaded

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-653-1250

Spring
Bolt Hole Quantity:
3 all ends
Maximum Operating Temp:
425.00 degrees fahrenheit 2nd response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.50 inches
Adjustable Pressure Range:
+13.00 to 23.00 pounds per square inch
Maximum Operating Pressure:
150.00 pounds per square inch 1st response
Outside Diameter:
3.25 inches all ends
First Connection Face To Centerline Distance:
2.50 inches
Bolt Hole Diameter:
0.563 inches all ends
Second Connection Face To Centerline Distance:
2.38 inches
Bolt Circle Diameter:
2.44 inches all ends
Flange Face Design:
Recessed straight all ends
Product Name:
Valve, angle relief
Material:
Steel comp 316 stem
Media For Which Designed:
Liquid single response

NSN 4820-01-653-1250

Safety Relief Valve - Page 2 of 2



	nator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0