## NSN 4910-00-441-8685



Pneumatic Tire Inflator-gage - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4910-00-441-8685 **Inside Diameter:** 0.250 inches **Outside Diameter:** 0.500 inches **Burst Test Pressure:** 175.0 pounds per square inch **End Application:** Mrap - cougar cat1 a1 **Indicator Type:** Inclosed self-contained cartridge Minimum Length: 10.000 feet **Indicator Operation Control Device:** Separate lever **Calibration Range:** +10.000 to 120.000 pounds **Smallest Graduated Division Per Range:** 2 lb **Chuck Type: Dual foot Chuck Valve Holding Clip:** Included **Deflating Position:** Included **Deflating Cock:** Included Oil Duct: Not included **Hose Coupler Quick Connection To Inflating Air Chuck Feature:** Included **Quick Connection Coupler Type:** Constant bleed **Long High Pressure Safety Hose:** Included **Accessory Type:** Tool and equipment **Special Features:** 1 bleeder vale between inflator gage and hose, 1 valve threaded 0.482-26 for chuck, Ig of item 132.000 plus or minus 3.000, issued without dual foot chuck Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 4910-00-441-8685

Pneumatic Tire Inflator-gage - Page 2 of 2



Demilitarization:

No

Fiig:

T273-c