## NSN 4920-00-028-3597

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-00-028-3597 **Hydraulic Fluid Flow Rate:** 5.0 gallons per minute **Current Type:** Ac **End Application:** Multi-aircraft systems age **Usage Design:** Aircraft hydraulic system Installation Design: Portable **Horsepower Rating:** 20.0 **Power Source:** Electric motor **Accumulator:** Not included **Pressure Rating:** 3000.0 pounds per square inch and 5000.0 pounds per square inch **Engine Driven Hydraulic Pump Testing Design Feature:** Not included **Pressure Manifold Subcircuit:** Not included Filtering System: Included Pressure/suction Hose: Included Voltage In Volts: 220.0 and 440.0 Phase: Three **Functional Classification:** Gg-5.3 **Special Features:** Single system Frequency In Hertz: 60.0 **Functional Description:** Designed to bleed air, drain, flush and refill the aircraft systems with micronically filtered hydraulic fluid **Reference Data And Literature:** 

T.O. 33a2-2-23-31

**Specification Or Standard:** 

D-6 type

## NSN 4920-00-028-3597

Hydraulic System Components Test Stand - Page 2 of 2



<b>Departure From Cited Document:</b>
Basic only
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

T361-e