NSN 4920-00-089-1025

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-00-089-1025

Hydraulic Fluid Flow Rate:
15.0 gallons per minute
Current Type:
Ac
End Application:
Multi-aircraft systems age
Usage Design:
Aircraft hydraulic system
Installation Design:
Portable
Horsepower Rating:
60.0
Power Source:
Electric motor
Accumulator:
Not included
Pressure Rating:
3000.0 pounds per square inch and 5000.0 pounds per square inch
Engine Driven Hydraulic Pump Testing Design Feature:
Not included
Pressure Manifold Subcircuit:
Not included
Filtering System:
Included
Pressure/suction Hose:
Included
Voltage In Volts:
220.0 and 440.0
Phase:
Three
Functional Classification:
Gg-5.3
Special Features:
Single system
Frequency In Hertz:
60.0
Functional Description:
Designed to bleed air, drain, flush and refill aircraft systems with micronically filtered hydraulic fluid
Reference Data And Literature:
T.O.33a2-2-23-31
Specification Or Standard:

Mk1 type

NSN 4920-00-089-1025

Hydraulic System Components Test Stand - Page 2 of 2



Shelf Li	fe:
----------	-----

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

Т361-е