NSN 4920-00-204-2569

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-00-204-2569 **Hydraulic Fluid Flow Rate:** 5.0 gallons per minute **Current Type:** Ac **Usage Design:** Aircraft hydraulic system Installation Design: Portable Horsepower Rating: 20.0 **Power Source:** Electric motor **Accumulator:** Not included **Pressure Rating:** 3000.0 pounds per square inch and 5000.0 pounds per square inch **Engine Driven Hydraulic Pump Testing Design Feature:** Not included **Pressure Manifold Subcircuit:** Not included Filtering System: Included Pressure/suction Hose: Included Voltage In Volts: 220.0 and 440.0 Phase: Three **Functional Classification:** Gg-5.3 **Special Features:** Single system Frequency In Hertz: 60.0 **Functional Description:** Used to bleed air, drain, flush andrefill the aircraft system with micronically filtered hydraulic fluid **Reference Data And Literature:** T.O.33a2-2-23-31 **Specification Or Standard:** D-6 type Shelf Life:

N/a

NSN 4920-00-204-2569

Hydraulic System Components Test Stand - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

Т361-е