

View Online at <https://aerobasegroup.com/nsn/4920-00-219-0080>

**Hydraulic Fluid Flow Rate:**

70.0 gallons per minute

**End Application:**

F-16 a/b/c/d

**Usage Design:**

Aircraft hydraulic system

**Installation Design:**

Fixed

**Power Source:**

Manual

**Accumulator:**

Not included

**Pressure Rating:**

3000.0 pounds per square inch

**Engine Driven Hydraulic Pump Testing Design Feature:**

Not included

**Pressure Manifold Subcircuit:**

Not included

**Filtering System:**

Included

**Pressure/suction Hose:**

Not included

**Voltage In Volts:**

110.0 and 220.0

**Phase:**

Single or three

**Functional Classification:**

Aa9.2

**Special Features:**

120.0 in w, 78.000 in l, 78.000 in h

**Frequency In Hertz:**

60.0 and 440.0

**Functional Description:**

Designed to performance test actuating cylinders, relief valves, selector valves, shuttle valves, servo valves and the like without connection to a drive and dynamometer console

**Entry Date:**

73-05-01

**Reference Data And Literature:**

T.O. 33d2-5-69-4

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T361-e