

View Online at <https://aerobasegroup.com/nsn/4920-00-288-1566>

End Application:

Multi aircraft application

Functional Classification:

Jj-7.1

Functional Description:

Provides air to aircraft cabins at controlled pressures for ground checking the cabins for leakage under pressurized conditions

Entry Date:

80-08-06

Reference Data And Literature:

T.O. 33a4-4-10-1 and 33a4-4-10-4

Relationship To Similar Equipment:

Use 4920006016926, consolidate from 2520003180464

General Description:

0portable; blower capacity, 2 psi min discharge pressure, 12.5 psi maximum discharge pressure, 10 cfm min vol of free air delivery, 200 cfm maximum vol of free air delivery; self-contained unit, electric motor operated, 10 hp, dc, 220 to 440v; over-all dim. Data, 48 to 60 in. Lg, 36 to 40 in. W, 39 in. Maximum h; accessories, 1 bushing to adapter, 38 to 1/4 in., 1 bushing to adapter, 1/2 to 3/8 in., 1 hose, 3/8 in. Diameter by 25 ft, 1 hose, 1/2 in. Diameter by 25 ft, 1 hose, 3 in. Diameter by 25 ft, 1 set, adapters and gaskets, 1 stethoscope

Type/model Designation:

Mb-3

Specification Or Standard:

Mb-3 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900