

View Online at <https://aerobasegroup.com/nsn/4920-00-339-0669>

**Hydraulic Fluid Flow Rate:**

15.0 gallons per minute

**Current Type:**

Ac

**Usage Design:**

Aircraft hydraulic system

**Installation Design:**

Portable

**Horsepower Rating:**

60.0

**Power Source:**

Electric motor

**Accumulator:**

Not included

**Pressure Rating:**

3000.0 pounds per square inch and 5000.0 pounds per square inch

**Engine Driven Hydraulic Pump Testing Design Feature:**

Not included

**Pressure Manifold Subcircuit:**

Not included

**Filtering System:**

Included

**Pressure/suction Hose:**

Included

**Voltage In Volts:**

220.0 and 440.0

**Phase:**

Three

**Functional Classification:**

Gg-5.3

**Frequency In Hertz:**

60.0

**Functional Description:**

Used to bleed air, drain, flush, and refill the aircraft system with micronically filtered hydraulic fluid

**Reference Data And Literature:**

T.O. 33a2-2-23-31

**Specification Or Standard:**

Mk1 type

**Fsc Application Data:**

C/ac/ec-130, c-123, c/vc-140, a-3-37a/b, kc-135, vc-135b, wc-135b, c-5a aircraft age

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T361-e