

View Online at <https://aerobasegroup.com/nsn/4920-00-339-0669>

Hydraulic Fluid Flow Rate:

15.0 gallons per minute

Current Type:

Ac

Usage Design:

Aircraft hydraulic system

Installation Design:

Portable

Horsepower Rating:

60.0

Power Source:

Electric motor

Accumulator:

Not included

Pressure Rating:

3000.0 pounds per square inch and 5000.0 pounds per square inch

Engine Driven Hydraulic Pump Testing Design Feature:

Not included

Pressure Manifold Subcircuit:

Not included

Filtering System:

Included

Pressure/suction Hose:

Included

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Functional Classification:

Gg-5.3

Frequency In Hertz:

60.0

Functional Description:

Used to bleed air, drain, flush, and refill the aircraft system with micronically filtered hydraulic fluid

Reference Data And Literature:

T.O. 33a2-2-23-31

Specification Or Standard:

Mk1 type

Fsc Application Data:

C/ac/ec-130, c-123, c/vc-140, a-3-37a/b, kc-135, vc-135b, wc-135b, c-5a aircraft age

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T361-e