

View Online at <https://aerobasegroup.com/nsn/4920-00-508-4082>

**Width:**

17.531 inches

**Length:**

19.531 inches

**Ac Voltage Rating:**

115.0 volts

**Frequency Rating:**

400.0 hertz

**Internal Battery Accommodation:**

Not included

**Material And Location:**

Aluminum carrying case

**Inclosure Feature:**

Single item w/carrying case

**Test Type For Which Designed:**

Measurement of voltage, current & frequency

**Operating Test Capability:**

Measurement of voltage, current and frequency; frequency meter, range 380 to 420 hertz, accuracy form 1 pct; microammeter, range 50-0-50 ua dc, 95 mv drop across terminals sensitivity; milliammeter, range 10-0-10 ma dc, 50 mv drop across terminals sensitivity; quality indicator, range 45-0-45 degrees sensitivi type 30 ua dc for 45 degrees deflection from null; variable transformer, input 115 vac, output 0 to 135 vac, max current 3 amp, frequency range 350 to 1200 hertz; voltmeter, range 0 to 15 vdc, sensitivi type 200 ohms per v; voltmeter, range 0 to 150 vac, sensitivi type 75 ohms per v, frequency 400 hertz

**Phase:**

Single

**Height:**

13.875 inches

**Fsc Application Data:**

Test set, specially designed, acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T228-a