

View Online at <https://aerobasegroup.com/nsn/4920-00-528-8780>

**Hydraulic Fluid Flow Rate:**

42.0 gallons per minute

**Current Type:**

Ac

**Usage Design:**

Aircraft hydraulic system

**Installation Design:**

Portable

**Horsepower Rating:**

60.0

**Power Source:**

Electric motor

**Accumulator:**

Not included

**Pressure Rating:**

2750.0 pounds per square inch and 4600.0 pounds per square inch

**Engine Driven Hydraulic Pump Testing Design Feature:**

Not included

**Pressure Manifold Subcircuit:**

Not included

**Filtering System:**

Included

**Pressure/suction Hose:**

Included

**Voltage In Volts:**

220.0 and 440.0

**Phase:**

Three

**Functional Classification:**

Gg-5.3

**Special Features:**

Two independent systems; trailer mounted; 0.0-27.0 gpm at pressure up to 3000.0 psig with a combined flow of 0.0-54.0 gpm at pressures up to 5000.0psig; thermal relief valve; high temp switch; low pressure switch; poppet type check valve and a low temp switch

**Frequency In Hertz:**

60.0

**Functional Description:**

Performance and operating characteristics

**Reference Data And Literature:**

T.O.33a2-2-22-11

**Specification Or Standard:**

Mk3a type

**Fsc Application Data:**

F/f-16, f-5, fb-111, f-105, e-4, b-57, a7d, a-10, c-141, and c-5 acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T361-e