

View Online at <https://aerobasegroup.com/nsn/4920-00-528-8780>

Hydraulic Fluid Flow Rate:

42.0 gallons per minute

Current Type:

Ac

Usage Design:

Aircraft hydraulic system

Installation Design:

Portable

Horsepower Rating:

60.0

Power Source:

Electric motor

Accumulator:

Not included

Pressure Rating:

2750.0 pounds per square inch and 4600.0 pounds per square inch

Engine Driven Hydraulic Pump Testing Design Feature:

Not included

Pressure Manifold Subcircuit:

Not included

Filtering System:

Included

Pressure/suction Hose:

Included

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Functional Classification:

Gg-5.3

Special Features:

Two independent systems; trailer mounted; 0.0-27.0 gpm at pressure up to 3000.0 psig with a combined flow of 0.0-54.0 gpm at pressures up to 5000.0psig; thermal relief valve; high temp switch; low pressure switch; poppet type check valve and a low temp switch

Frequency In Hertz:

60.0

Functional Description:

Performance and operating characteristics

Reference Data And Literature:

T.O.33a2-2-22-11

Specification Or Standard:

Mk3a type

Fsc Application Data:

F/f-16, f-5, fb-111, f-105, e-4, b-57, a7d, a-10, c-141, and c-5 acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T361-e