

View Online at https://aerobasegroup.com/nsn/4920-00-618-8993

Hydraulic Fluid Flow Rate:

22.5 gallons per minute

Usage Design:

Aircraft hydraulic system

Installation Design:

Portable

Horsepower Rating:

150.0

Power Source:

Gasoline engine

Accumulator:

Not included

Pressure Rating:

3000.0 pounds per square inch and 5000.0 pounds per square inch

Engine Driven Hydraulic Pump Testing Design Feature:

Not included

Pressure Manifold Subcircuit:

Not included

Filtering System:

Included

Pressure/suction Hose:

Included

Special Features:

Portable; two identical systems; adjustable pressure-compensator control; low pressure boost pumps; check valves; thermoswitches;

interlock system; shutoff valves and blowout devices; powered by engine-driven dc generator with two 24.0 vdc, 36 ampere hour batteries

Functional Description:

Hydraulic testing

Reference Data And Literature:

T.O.33a2-2-24-11

Specification Or Standard:

Mj2a type

Fsc Application Data:

E-4, f-111, a7d, c-5, f-101, f-16, f-106, t-38, c-135 aircraft age

Departure From Cited Document:

Revision a

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

Т361-е