NSN 4920-00-707-7443

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-00-707-7443 **Hydraulic Fluid Flow Rate:** 30.0 gallons per minute **Current Type:** Ac **Usage Design:** Aircraft hydraulic system Installation Design: Portable **Horsepower Rating:** 60.0 **Power Source:** Electric motor **Accumulator:** Not included **Pressure Rating:** 3000.0 pounds per square inch and 5000.0 pounds per square inch **Engine Driven Hydraulic Pump Testing Design Feature:** Not included **Pressure Manifold Subcircuit:** Included **Subcircuit Quantity And Maximum Operating Pressure:** Two 5000 psi Filtering System: Included Pressure/suction Hose: Included Voltage In Volts: 220.0 and 440.0 Phase: Three **Functional Classification:** Gg-5.3 **Special Features:** Two independent systems w/manifold capabilities Frequency In Hertz: 60.0 **Reference Data And Literature:** 33a2-2-31-4 **Specification Or Standard:** Mk3 type

Departure From Cited Document: Basic only

NSN 4920-00-707-7443

Hydraulic System Components Test Stand - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

Т361-е