NSN 4920-00-764-5527

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-00-764-5527 **Hydraulic Fluid Flow Rate:** 15.0 gallons per minute **Current Type:** Ac **Usage Design:** Aircraft hydraulic system Installation Design: Portable **Horsepower Rating:** 60.0 **Power Source:** Electric motor **Accumulator:** Not included **Pressure Rating:** 2750.0 pounds per square inch and 4600.0 pounds per square inch **Engine Driven Hydraulic Pump Testing Design Feature:** Not included **Pressure Manifold Subcircuit:** Included **Subcircuit Quantity And Maximum Operating Pressure:** Two 5000 psi Filtering System: Included Pressure/suction Hose: Included Voltage In Volts: 220.0 and 440.0 Phase: Three **Functional Classification:** Gg-5.3 **Special Features:** Two independent systems w/manifold capacilities Frequency In Hertz: 60.0 **Reference Data And Literature:** T.O.33a2-2-30-1 **Specification Or Standard:** Mk3a type

N/a

Shelf Life:

NSN 4920-00-764-5527

Hydraulic System Components Test Stand - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

Т361-е