NSN 4920-00-857-6895

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-00-857-6895

Hydraulic Fluid Flow Rate:
70.0 gallons per minute
Current Type:
Ac
Drive Type:
Hydraulic motor
Usage Design:
Aircraft hydraulic system
Installation Design:
Fixed
Power Source:
Electric motor
Maximum Speed Rating In Rpm:
15000.0
Accumulator:
Included
Pressure Rating:
5000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Engine Driven Hydraulic Pump Testing Design Feature:
Included
Flow Capacity Rating:
85.0 gallons per minute
Pressure Manifold Subcircuit:
Not included
Filtering System:
Included
Pressure/suction Hose:
Included
Voltage In Volts:
110.0 and 220.0
Phase:
Single
Special Features:
80.000 in h, 66.000 in d, 168.000 in l; 14760.0 lbs
Frequency In Hertz:
400.0
Functional Description:
Designed to provide accurate, functional and performance testing of aircraft hydraulic fixed and variable pumps, hydraulic motors, valves

T.O. 33a2-2-35-11

Reference Data And Literature:

actuating cylinders, reservoirs, and accumulators

NSN 4920-00-857-6895

Hydraulic System Components Test Stand - Page 2 of 2



Shelf	Life
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

Т361-е