

View Online at <https://aerobasegroup.com/nsn/4920-00-919-3130>

Hydraulic Fluid Flow Rate:

20.0 gallons per minute

Current Type:

Ac

Drive Type:

Electric motor

Usage Design:

Aircraft hydraulic system

Installation Design:

Fixed

Horsepower Rating:

0.5

Power Source:

Electric motor

Maximum Speed Rating In Rpm:

1725.0

Accumulator:

Included

Pressure Rating:

Between 1000.0 pounds per square inch and 3000.0 pounds per square inch

Maximum Operating Pressure:

5000.0 pounds per square inch

Engine Driven Hydraulic Pump Testing Design Feature:

Included

Flow Capacity Rating:

20.0 gallons per minute

Pressure Manifold Subcircuit:

Not included

Filtering System:

Included

Pressure/suction Hose:

Included

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Power pack allows system to be a dual system; control section is 45.000 in w, 87.000 in h, 96.000 in l; power pack 76.000 in w, 66.000 in h, 64.000 in l

Frequency In Hertz:

60.0

Functional Description:

Provides hydraulic power to test the spoiler actuation system of the c-141 aircraft

Reference Data And Literature:

T.O. 33d2-5-37-1

Fsc Application Data:

C-141 aircraft age

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T361-e