

View Online at <https://aerobasegroup.com/nsn/4920-00-919-3130>

**Hydraulic Fluid Flow Rate:**

20.0 gallons per minute

**Current Type:**

Ac

**Drive Type:**

Electric motor

**Usage Design:**

Aircraft hydraulic system

**Installation Design:**

Fixed

**Horsepower Rating:**

0.5

**Power Source:**

Electric motor

**Maximum Speed Rating In Rpm:**

1725.0

**Accumulator:**

Included

**Pressure Rating:**

Between 1000.0 pounds per square inch and 3000.0 pounds per square inch

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Engine Driven Hydraulic Pump Testing Design Feature:**

Included

**Flow Capacity Rating:**

20.0 gallons per minute

**Pressure Manifold Subcircuit:**

Not included

**Filtering System:**

Included

**Pressure/suction Hose:**

Included

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Power pack allows system to be a dual system; control section is 45.000 in w, 87.000 in h, 96.000 in l; power pack 76.000 in w, 66.000 in h, 64.000 in l

**Frequency In Hertz:**

60.0

**Functional Description:**

Provides hydraulic power to test the spoiler actuation system of the c-141 aircraft

**Reference Data And Literature:**

T.O. 33d2-5-37-1

**Fsc Application Data:**

C-141 aircraft age

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T361-e