NSN 4920-00-995-8037Flight Control System Test Set - Page 1 of 1



| Width: 15.000 inches Length: 16.000 inches Ac Voltage Rating: 115.000 volts Cc Voltage Rating: 27.000 volts Frequency Rating: 400.000 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system Phase: |
|--|
| Length: 16.000 inches Ac Voltage Rating: 115.000 volts Dc Voltage Rating: 27.000 volts Frequency Rating: 400.000 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Ac Voltage Rating: 115.000 volts Dc Voltage Rating: 27.000 volts Frequency Rating: 400.000 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Ac Voltage Rating: 115.000 volts Dc Voltage Rating: 27.000 volts Frequency Rating: 400.000 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Into the control of t |
| Dc Voltage Rating: 27.000 volts Frequency Rating: 400.000 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| 27.000 volts Frequency Rating: 400.000 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Frequency Rating: 400.000 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Atternal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Not included Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Material And Location: Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Aluminum carrying case Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Inclosure Feature: Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Single item w/carrying case Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Test Type For Which Designed: Test and troubleshoot the afcs; mcm coupler system |
| Test and troubleshoot the afcs; mcm coupler system |
| |
| Phase: |
| |
| Single |
| Functional Description: |
| Provides a means of checking the operation of the automatic flight control syste (afcs) without removal of system components from sikorsky |
| model hh-53b/c helicopter |
| Height: |
| 16.000 inches |
| Reference Data And Literature: |
| Го 33d3-9-141-1 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Filg: |
| Г228-а |