## NSN 4920-01-007-9052

Hydraulic Pumping Unit Test Stand - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4920-01-007-9052

Hydraulic Fluid Flow Rate: 5.0 gallons per minute  End Application: F-15 acft  Usage Design: Aircraft hydraulic system Installation Design: Fixed  Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch  Engine Driven Hydraulic Pump Testing Design Feature: Not included  Functional Classification: Aa-9.3  Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature: T.O. 33da35-3-1  Supplementary Features:
End Application: F-15 acft Usage Design: Aircraft hydraulic system Installation Design: Fixed Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch Engine Driven Hydraulic Pump Testing Design Feature: Not included Functional Classification: Aa-9.3 Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly Reference Data And Literature: T.O. 33da35-3-1
F-15 acft  Usage Design: Aircraft hydraulic system Installation Design: Fixed  Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch  Engine Driven Hydraulic Pump Testing Design Feature: Not included  Functional Classification: Aa-9.3  Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature: T.O. 33da35-3-1
Usage Design: Aircraft hydraulic system Installation Design: Fixed Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch Engine Driven Hydraulic Pump Testing Design Feature: Not included Functional Classification: Aa-9.3 Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly Reference Data And Literature: T.O. 33da35-3-1
Aircraft hydraulic system  Installation Design: Fixed  Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch  Engine Driven Hydraulic Pump Testing Design Feature:  Not included  Functional Classification:  Aa-9.3  Special Features:  Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description:  Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Installation Design: Fixed  Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch  Engine Driven Hydraulic Pump Testing Design Feature: Not included  Functional Classification: Aa-9.3  Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature: T.O. 33da35-3-1
Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch Engine Driven Hydraulic Pump Testing Design Feature: Not included Functional Classification: Aa-9.3 Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly Reference Data And Literature: T.O. 33da35-3-1
Pressure Rating: Between 0.000 pounds per square inch and 5000.000 pounds per square inch  Engine Driven Hydraulic Pump Testing Design Feature:  Not included  Functional Classification:  Aa-9.3  Special Features:  Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description:  Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Between 0.000 pounds per square inch and 5000.000 pounds per square inch  Engine Driven Hydraulic Pump Testing Design Feature:  Not included  Functional Classification:  Aa-9.3  Special Features:  Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description:  Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Engine Driven Hydraulic Pump Testing Design Feature:  Not included  Functional Classification:  Aa-9.3  Special Features:  Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description:  Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Not included  Functional Classification:  Aa-9.3  Special Features:  Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description:  Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Functional Classification:  Aa-9.3  Special Features:  Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description:  Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature: T.O. 33da35-3-1
Special Features: Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature: T.O. 33da35-3-1
Weight 800.000 lbs; dim's, 138.000 in. L, 42.000 in. W, 72.000 in. H  Functional Description:  Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Functional Description: Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Used to provide hydraulic pressure for csbpc overhaul and testing whichc/o pitch and roll channel assembly (prca) and the aileron rudder interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
interconnect (ari) assembly  Reference Data And Literature:  T.O. 33da35-3-1
Reference Data And Literature: T.O. 33da35-3-1
T.O. 33da35-3-1
Supplementary Features:
Company item name-console, hydraulic, (csbpc)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T361-e