NSN 4920-01-044-5926

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-01-044-5926 **Hydraulic Fluid Flow Rate:** 60.0 gallons per minute **Current Type:** Ac **Drive Type:** Electric motor **Usage Design:** Aircraft hydraulic system Installation Design: Portable **Horsepower Rating:** 40.0 **Circuit Type:** Booster cylinder **Power Source:** Electric motor **Maximum Speed Rating In Rpm:** 3600.0 **Accumulator:** Not included **Pressure Rating:** 6000.0 pounds per square inch **Maximum Operating Pressure:** 6000.0 pounds per square inch **Engine Driven Hydraulic Pump Testing Design Feature:** Included Flow Capacity Rating: 30.0 gallons per minute **Pressure Manifold Subcircuit:** Included **Subcircuit Quantity And Maximum Operating Pressure:** One 50 psi **Circuit Pressure Rating:** 50.0 pounds per square inch Filtering System: Included Pressure/suction Hose: Included Voltage In Volts: 440.0

Phase: Three

NSN 4920-01-044-5926

Hydraulic System Components Test Stand - Page 2 of 2



Functional Classification:
Aa-9.2
Frequency In Hertz:
60.0
Functional Description:
Used to test aircraft hydraulic systems/components without operating aircraft or removing components
Reference Data And Literature:
T.O. 33d2-5-39-1
Fsc Application Data:
F-15 and f/rf-4 aircraft age
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
T361-e