

View Online at <https://aerobasegroup.com/nsn/4920-01-144-8385>

**Hydraulic Fluid Flow Rate:**

30.0 gallons per minute

**End Application:**

B1-b aircraft age.

**Usage Design:**

Individual hydraulic units

**Installation Design:**

Fixed

**Accumulator:**

Not included

**Engine Driven Hydraulic Pump Testing Design Feature:**

Not included

**Pressure Manifold Subcircuit:**

Not included

**Filtering System:**

Included

**Functional Classification:**

Gg-7.3

**Special Features:**

Test stand c/o two sections bolted together and remote drive cabinet; 7 ft. Deep, 14.000 ft. Lg, 6.500 ft h; contains 100 hp d.C. Drive motor, oil resevior, supply pumps, instrumentation, and other hydraulic and pneumatic component required for testing of the hydraulic pump; must be installed in a non-harzardous area; electrical system req 480v/30/60 hz/4 wire, other electrical controls 110 volt/10 power obtained from step down transformer located in the stand electrical cabinet

**Functional Description:**

Test hyd pum p/n 9798m64p09

**Reference Data And Literature:**

T.O. 33d4-6-676-1; serd 0507

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T361-e