

View Online at <https://aerobasegroup.com/nsn/4920-01-148-4198>

**End Application:**

An/avq-26 (pave tack); rf-4c, f-4e, f-111f

**Special Features:**

Operating temperature 65.0 to 85.0 deg. "f", 18.0 5 to 29.0 deg. "c"; operating humidity type 45.0 percent at 70.0 deg. "f"; storage temperature 65.0 to 85.0 deg. "f, 18.0 to 29.0 deg. "c"; storage humidity type 45.0 percent at 70.0 deg. "f"; vac. 115.0 to 480.0 ac; frequency 60.0 to 400.0 hertz; 1 to 3 phase; power consumption 5.0 to 76.0 kva; power consumption volt-amps 60 to 115

**Reference Data And Literature:**

T.O. 35d5-12-224-1

**General Description:**

C/o 8 test areas: (1)mirror control dynamic test stand, (2)mirror control disassembly/assembly area, (3)inner gimbal group repair area (gra), (4)inertia balancer gra, (5)mirror assembly gra, (6)outer gimbal structure gra, (7)base assembly gra, (8)autocollimator gra; used to test mirror control (c-10226a/avq-26) part no. 126801

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A23900