## NSN 4920-01-262-1413

**Hydraulic Fluid Flow Rate:** 

Hydraulic Pumping Unit Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-01-262-1413

| 135.0 gallons per minute  |
|---|
| Current Type:   |
| Dc  |
| Drive Type:   |
| Hydraulic motor   |
| Usage Design:   |
| Aircraft hydraulic system   |
| Installation Design:  |
| Portable  |
| Horsepower Rating:  |
| Not rated   |
| Power Source:   |
| Electric motor  |
| Maximum Speed Rating In Rpm:  |
| Not rated   |
| Accumulator:  |
| Included  |
| Pressure Rating:  |
| 4000.0 pounds per square inch   |
| Maximum Operating Pressure:   |
| 4250.0 pounds per square inch   |
| Engine Driven Hydraulic Pump Testing Design Feature:  |
| Included  |
| Flow Capacity Rating:   |
| 64.5 gallons per minute   |
| Pressure Manifold Subcircuit:   |
| Not included  |
| Filtering System:   |
| Included  |
| Pressure/suction Hose:  |
| Included  |
| Voltage In Volts:   |
| Not rated   |
| Special Features:   |
| 72 in. H, 60 in. W, 96 in. D,; used on b1-b acft  |
| Functional Description:   |
| Provides hydraulic fluid hook-up, pressure and flow capacity, torque sensing, elec stimuli, controls, and computerized monitoring capability to   |
| fault isolate, adjust and verify the operational integrity of the engine driven hydraulic pump lru; also tests the electrically operated solenoid |
| for dielectric withstanding voltage   |
| Reference Data And Literature:  |
| Serd no. 450376   |
| Shelf Life:   |
| N/a   |

## NSN 4920-01-262-1413

Hydraulic Pumping Unit Test Stand - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

Т361-е