NSN 4920-01-262-1413

Hydraulic Fluid Flow Rate:

Hydraulic Pumping Unit Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-01-262-1413

135.0 gallons per minute
Current Type:
Dc
Drive Type:
Hydraulic motor
Usage Design:
Aircraft hydraulic system
Installation Design:
Portable
Horsepower Rating:
Not rated
Power Source:
Electric motor
Maximum Speed Rating In Rpm:
Not rated
Accumulator:
Included
Pressure Rating:
4000.0 pounds per square inch
Maximum Operating Pressure:
4250.0 pounds per square inch
Engine Driven Hydraulic Pump Testing Design Feature:
Included
Flow Capacity Rating:
64.5 gallons per minute
Pressure Manifold Subcircuit:
Not included
Filtering System:
Included
Pressure/suction Hose:
Included
Voltage In Volts:
Not rated
Special Features:
72 in. H, 60 in. W, 96 in. D,; used on b1-b acft
Functional Description:
Provides hydraulic fluid hook-up, pressure and flow capacity, torque sensing, elec stimuli, controls, and computerized monitoring capability to
fault isolate, adjust and verify the operational integrity of the engine driven hydraulic pump lru; also tests the electrically operated solenoid
for dielectric withstanding voltage
Reference Data And Literature:
Serd no. 450376
Shelf Life:
N/a

NSN 4920-01-262-1413

Hydraulic Pumping Unit Test Stand - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

Т361-е