

View Online at <https://aerobasegroup.com/nsn/4920-01-272-9620>

Hydraulic Fluid Flow Rate:

60.0 gallons per minute

Current Type:

Ac

End Application:

B-2 acft

Drive Type:

Electric motor

Usage Design:

Aircraft hydraulic system

Installation Design:

Portable

Horsepower Rating:

Not rated

Power Source:

Electric motor

Maximum Speed Rating In Rpm:

Not rated

Accumulator:

Not included

Pressure Rating:

Between 0.0 pounds per square inch and 5000.0 pounds per square inch

Maximum Operating Pressure:

Not rated

Engine Driven Hydraulic Pump Testing Design Feature:

Included

Flow Capacity Rating:

Not rated

Pressure Manifold Subcircuit:

Not included

Subcircuit Quantity And Maximum Operating Pressure:

Two 5000 psi

Filtering System:

Included

Pressure/suction Hose:

Not included

Voltage In Volts:

380.0 and 480.0

Phase:

Three

Special Features:

C/o trailer mounted, towable and steerable; combination lifting & tiedown eyes; forklift channels; weight: 6,000 lbs; hydraulic fluid is mil-h-5606; operating degrees: m40 to p160; hydraulic fluid conditioning: 1 per cent dissolved air ; 100 ppm water ; nas 1638, class 4 particles; four 20 in. Wheels; 60 psi pneumatic tire, 6x9, 10 ply; 66.5 in. Wheelbase; dim: 116 in. Lg; 79 in. W; 70 in. H

Frequency In Hertz:

50.0 and 60.0

Functional Description:

Used to check the performance and operating characteristics of aircraft hydraulic systems

Reference Number Differentiating Characteristics:

Source control item, repairable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T361-e