

View Online at <https://aerobasegroup.com/nsn/4920-01-320-9519>

**Hydraulic Fluid Flow Rate:**

35.0 gallons per minute

**Current Type:**

Ac

**End Application:**

Power drive unit, p/n 2022070 and 2048666, used on the f-16a/b/c/d/

**Drive Type:**

Hydraulic motor

**Usage Design:**

Aircraft hydraulic system

**Installation Design:**

Fixed

**Power Source:**

Electric motor or manual

**Maximum Speed Rating In Rpm:**

150.0

**Accumulator:**

Not included

**Pressure Rating:**

4600.0 pounds per square inch

**Maximum Operating Pressure:**

4600.0 pounds per square inch

**Engine Driven Hydraulic Pump Testing Design Feature:**

Included

**Flow Capacity Rating:**

15.8 gallons per minute

**Pressure Manifold Subcircuit:**

Not included

**Filtering System:**

Included

**Pressure/suction Hose:**

Not included

**Voltage In Volts:**

115.0

**Phase:**

Single

**Functional Classification:**

Aa-9.2

**Special Features:**

C/o three separate units, interfaced to one another by electrical cables; first unit is a hydraulic test bench, dim. 90.000 in. W; 50.000 in. D; 55.000 in. H; weight: 5000 lbs; the second unit is a instrumentation and control console, dim. 62.000 in. H; 40.000 in. W; 40.000 in. D; weight: 500 lbs; power: 115 v, 60 hz, single phase 20 amps; the third unit is a computer and printer, dim. On the crt are 18.000 in. H; 18.000 in. W; 7.000 in. D; the dim. On the keyboard are 3.000 in. H; 18.000 in. W; 7.000 in. D

**Frequency In Hertz:**

60.0

**Functional Description:**

Used to check out the leading edge flap, power drive unit

**Entry Date:**

90-05-21

**Reference Data And Literature:**

Serd-14025

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T361-e