NSN 4920-01-399-6785

Aircraft Maintenance Rigging Kit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4920-01-399-6785

| End Application: |
|---|
| C-17 core thrust reverser |
| Unpackaged Unit Length: |
| 25.000 inches |
| Unpackaged Unit Width: |
| 24.000 inches |
| Unpackaged Unit Height: |
| 12.000 inches |
| Special Features: |
| Consists of 2 pairs rigging spacers, 18 in. Long, 2 in. Wide, 6 in. High; 1 rigging bar 40 in. Long, 3 in. Wide, 0.25 in. High, aluminum, 3 |
| lbs; 1 actuator lock 18 in. Long, 4 in. Wide, 5 lbs, steel; 7 blocker door spacers, 1.500 in. Long, 1 in. Wide, 0.75 in. Deep, 0.25 lbs, |
| steel; includes a case 25 in. Long, 24 in. Wide, 12 in. Deep, 15 lbs, plastic outer shell with foam cutout inserts |
| Functional Description: |
| G2 pairs of rigging spacers are used to adjust the travel length of the translating sleeve; the rigging bar is used to set the distance between |
| the fixed body and translating sleeve; the actuator lock provides locking of core thrust reverser actuator to maintain maximum extention |
| during rigging task; blocker door spacers are used to gauge to set step between blocker door outer surface and translating sleeve inner |
| surface to compensate for thermal expansion |
| Reference Data And Literature: |
| Serd 230253 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A23800 |
| |
| |