NSN 4920-01-502-2587

Hydraulic System Components Test Stand - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4920-01-502-2587 **Hydraulic Fluid Flow Rate:** 38.0 gallons per minute **Current Type:** Ac **Furnished Items And Quantity:** Fluid heat exchanger 1; tow bar 1; 42 gpm boost pump **Usage Design:** Aircraft hydraulic system Installation Design: Portable **Horsepower Rating:** 100.0 **Power Source:** Electric motor **Accumulator:** Included **Pressure Rating:** 4000.0 pounds per square inch **Engine Driven Hydraulic Pump Testing Design Feature:** Not included **Pressure Manifold Subcircuit:** Not included Filtering System: Included Pressure/suction Hose: Included **Product Name:** Portable hydraulic test stand, dual system Voltage In Volts: 230.0 and 380.0 and 460.0 Phase: Three **Special Features:** L116.0, w77.0, h74.0 inches; uses two 100 ho elec motors; supports f-22 aircraft Frequency In Hertz: 50.0 and 60.0 Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 4920-01-502-2587

Hydraulic System Components Test Stand - Page 2 of 2



Fiig:

Т361-е