

View Online at <https://aerobasegroup.com/nsn/4920-01-559-7446>

Hydraulic Fluid Flow Rate:

40.0 gallons per minute

Current Type:

Ac

End Application:

General aircraft

Usage Design:

Aircraft hydraulic system

Installation Design:

Portable

Power Source:

Electric motor

Accumulator:

Not included

Pressure Rating:

Between 250.0 pounds per square inch and 5000.0 pounds per square inch

Engine Driven Hydraulic Pump Testing Design Feature:

Not included

Pressure Manifold Subcircuit:

Included

Subcircuit Quantity And Maximum Operating Pressure:

Two 5000psi

Filtering System:

Included

Product Name:

Universal hydraulic test stand-dual system, trailer mounted

Voltage In Volts:

380.0 and 416.0

Phase:

Three

Functional Classification:

Aa-9.3

Frequency In Hertz:

50.0 and 60.0

Functional Description:

Type 2 dual system electric motor driven universal hydraulic test stand used in ground checking and maintenance of aircraft hydraulic systems

Reference Data And Literature:

Pd07wrgbzoenf10

Test Data Document:

98752-pd07wrgbzoenf10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T361-e