

View Online at <https://aerobasegroup.com/nsn/4920-01-559-7446>

**Hydraulic Fluid Flow Rate:**

40.0 gallons per minute

**Current Type:**

Ac

**End Application:**

General aircraft

**Usage Design:**

Aircraft hydraulic system

**Installation Design:**

Portable

**Power Source:**

Electric motor

**Accumulator:**

Not included

**Pressure Rating:**

Between 250.0 pounds per square inch and 5000.0 pounds per square inch

**Engine Driven Hydraulic Pump Testing Design Feature:**

Not included

**Pressure Manifold Subcircuit:**

Included

**Subcircuit Quantity And Maximum Operating Pressure:**

Two 5000psi

**Filtering System:**

Included

**Product Name:**

Universal hydraulic test stand-dual system, trailer mounted

**Voltage In Volts:**

380.0 and 416.0

**Phase:**

Three

**Functional Classification:**

Aa-9.3

**Frequency In Hertz:**

50.0 and 60.0

**Functional Description:**

Type 2 dual system electric motor driven universal hydraulic test stand used in ground checking and maintenance of aircraft hydraulic systems

**Reference Data And Literature:**

Pd07wrgbzoenf10

**Test Data Document:**

98752-pd07wrgbzoenf10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T361-e