

View Online at <https://aerobasegroup.com/nsn/4920-01-587-7138>

Hydraulic Fluid Flow Rate:

60.0 gallons per minute

Current Type:

Ac

Drive Type:

Electric motor

Usage Design:

Aircraft hydraulic system

Installation Design:

Portable

Horsepower Rating:

40.0

Circuit Type:

Booster cylinder

Power Source:

Electric motor

Maximum Speed Rating In Rpm:

3600.0

Accumulator:

Not included

Pressure Rating:

6000.0 pounds per square inch

Maximum Operating Pressure:

6000.0 pounds per square inch

Engine Driven Hydraulic Pump Testing Design Feature:

Included

Flow Capacity Rating:

30.0 gallons per minute

Pressure Manifold Subcircuit:

Included

Subcircuit Quantity And Maximum Operating Pressure:

One 50 psi

Circuit Pressure Rating:

50.0 pounds per square inch

Filtering System:

Included

Pressure/suction Hose:

Included

Voltage In Volts:

440.0

Phase:

Three

Functional Classification:

Aa-9.2

Frequency In Hertz:

60.0

Functional Description:

Used to test aircraft hydraulic systems/components without operating aircraft or removing components

Reference Data And Literature:

To 33d2-5-39-1

Relationship To Similar Equipment:

REFU-RB-ISH-ED49

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T361-e