

View Online at <https://aerobasegroup.com/nsn/4930-00-277-1633>

Discharge Connection Quantity:

2

Current Type:

Ac

Pump Quantity:

2

Operating Position:

Horizontal

Discharge Connection Type:

Flanged

Electric Motor Horsepower Rating:

10.0

Liquid Circulating Pump Type:

Radial flow

Maximum Fueling Capacity Rating:

150.0 gallons per minute

Fueling Operating Speed At Rated Capacity In Rpm:

1725.0

Err Default:

Err default

Maximum Defueling Capacity Rating:

100.0 gallons per minute

Defueling Operating Speed At Rated Capacity In Rpm:

1725.0

Suction Connection Characteristic:

Separate

Suction Connection Type:

Flanged

Suction Connection Quantity:

2

Electric Motor Manufacturer Code:

64123

Electric Motor Rpm:

1725.0

Primer Pump:

Included

Electric Motor Inclosure Type Per Specification Document:

Watertight per mil-std-108a

Air Eliminator:

Included

Magnetic Amplifier:

Included

Suction Connection Size:

3.000 n std

Discharge Connection Size:

2.500 n std

Separate Electric Motor:

Not included

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Quantity:

2

Reference Number Differentiating Characteristics:

Watertight motor enclosure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-a