

View Online at <https://aerobasegroup.com/nsn/4930-00-277-1634>

Discharge Connection Quantity:

2

Current Type:

Ac

Pump Quantity:

2

Operating Position:

Horizontal

Discharge Connection Type:

Flanged

Electric Motor Horsepower Rating:

12.5

Liquid Circulating Pump Type:

Radial flow

Maximum Fueling Capacity Rating:

150.0 gallons per minute

Fueling Operating Speed At Rated Capacity In Rpm:

3450.0

Maximum Defueling Capacity Rating:

100.0 gallons per minute

Defueling Operating Speed At Rated Capacity In Rpm:

3450.0

Suction Connection Characteristic:

Common

Suction Connection Type:

Flanged

Electric Motor Manufacturer Code:

07524

Electric Motor Rpm:

3450.0

Primer Pump:

Included

Electric Motor Inclosure Type Per Specificationified Document:

Explosion proof mil-std-108 or fan cooled mil-std-108

Air Eliminator:

Included

Magnetic Amplifier:

Included

Suction Connection Size:

4.000 n std

Discharge Connection Size:

2.500 n std

Separate Electric Motor:

Included

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Quantity:

2

Reference Number Differentiating Characteristics:

Explosion proof motors

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-a