NSN 4930-00-537-8977

Hand Oiler - Page 1 of 2





Body Material:

Steel

Body Style:

Bell shaped bench

Body Surface Treatment:

Any acceptable

Length:

Between 7.000 inches and 9.000 inches

Spout Style Designator:

Flexible-angle tip

Feed Type:

Compressible surface

Capacity:

8.000 ounces

Screw Thread Location:

External

Bottom Diameter:

Between 3.000 inches and 4.000 inches

Spout Style Designator:

B32

Spout Material:

Steel

Spout Surface Treatment:

Any acceptable

Spout Bottom End Thread Provision:

Threaded

Spout Closure Cap:

Not included

Check Valve Control Lever:

Not included

Holder Bracket:

Not included

Spout Tip Removability:

Nonremovable

Special Features:

W/s: nimitz class cvn; mortar, 60mm, m224; grader, road motorized, 130-g; generator, smoke; lpd-17 class amphibious transport dock; kidd class ddg; ticonderoga class cg (47); spruance class dd (963); forrestal class cv; mortar, 4.2in, m30, on mount, m-24 series

Specification Or Standard:

I type and a class

Shelf Life:

N/a

Unit Of Measure:

NSN 4930-00-537-8977

Hand Oiler - Page 2 of 2

Demilitarization:

No

Fiig:

T293-g

