

View Online at <https://aerobasegroup.com/nsn/4930-00-640-2421>

**Discharge Connection Quantity:**

2

**Current Type:**

Ac

**Pump Quantity:**

2

**Operating Position:**

Horizontal

**Discharge Connection Type:**

Flanged

**Electric Motor Horsepower Rating:**

20.0

**Liquid Circulating Pump Type:**

Radial flow

**Maximum Fueling Capacity Rating:**

200.0 gallons per minute

**Fueling Operating Speed At Rated Capacity In Rpm:**

3450.0

**Err Default:**

Err default

**Maximum Defueling Capacity Rating:**

100.0 gallons per minute

**Defueling Operating Speed At Rated Capacity In Rpm:**

3450.0

**Suction Connection Characteristic:**

Common

**Suction Connection Type:**

Flanged

**Electric Motor Manufacturer Code:**

50380

**Electric Motor Rpm:**

3450.0

**Primer Pump:**

Included

**Electric Motor Inclosure Type Per Specification Document:**

Explosion proof mil-std-108 or fan cooled mil-std-108

**Air Eliminator:**

Included

**Magnetic Amplifier:**

Included

**Suction Connection Size:**

4.000 n std

**Discharge Connection Size:**

2.500 n std

**Separate Electric Motor:**

Included

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Quantity:**

2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-a