

View Online at <https://aerobasegroup.com/nsn/4930-01-175-1425>

**Drive Connection Type:**

Gear

**Maximum Discharge Flow Rate:**

70.0 gallons per minute

**Nonsparking Provision:**

Included

**Controller:**

Included

**End Connection Type:**

Female tapered pipe threaded

**Pressure Capacity:**

300.0 pounds per square inch

**Clutch:**

Not included

**Installation Location:**

Right hand

**Mounting Facility:**

Floor

**Hose Length Accommodated:**

55.000 feet

**Hose Diameter Accommodated:**

1.500 inches

**Reel Rim Outside Diameter:**

30.000 inches

**Reel Hub Width:**

7.500 inches

**Fixed Reel Hose Piping Connection Type:**

Swing joint

**Motor Switch:**

Not included

**Mounting Plate Width:**

28.500 inches

**Hub Center Line Height Above Base:**

17.000 inches

**Reel Actuation Method:**

Manual

**Special Features:**

Used on nsn 2320-01-097-0249 m978 hemtt; w/right bottom rewind

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T293-h